

Nirantar UPS-621V



Features

- 33% Faster recharging
- Protects you from data loss
- Wide input voltage range
- Generator compatible
- Automatic voltage regulator for Boost & Buck
- Auto restart while AC recovery
- Green Power Function for energy saving.

Input Voltage

230VAC

Input Frequency

45-65 Hz (Auto Sensing)

Output Voltage Regulation (Batt.)

195-253V

Output Frequency Regulation (Batt.)

+/- 1Hz

Recharge Time

6 hours to 90% at normal mode

LED Indicator

Green LED for various indication modes

Power Outlets

5-Pin x 3

Operating Environment

0°C - 40°C

Warranty

2 Years (1 Year for battery)

Warranty

2 Years (1 Year for battery)

Battery Type

12V7AH x 1

Dimension (D x W x H)

287 x 100 x 142 mm

Microprocessor Controlled

Microprocessor controlled to guarantee high reliability

Input Voltage Range

140-300VAC

Output Voltage

230VAC

Output Frequency

50Hz or 60Hz

Output Waveform

Modified Sine-wave

Transfer Time

4-8ms

Full Protection

Discharge, overcharge, and overload protection

Net Weight

4.25 Kg.

Noise Level

Less than 40dB

Warranty

2 Years (1 Year for battery)

Capacity

600VA/360W

Audible Alarm

Beeper with various beeper modes